



SUGGESTED PANEL CUTOUT



SCHMATIC



SPECIFICATIONS

FUNCTION:  
2P1T OFF-ON  
Auto OFF Below Calibration Voltage

RATINGS:  
ANSI/UL 508 and CAN/CSA C22.2 No.14 (E195908):  
16A 220-240VAC [cURus]  
2HP 220-240VAC (12A FLA, 72A LRA) [cURus]

CALIBRATION VOLTAGE:  
Use: 240V 50Hz  
Release: 130-170V

ELECTRICAL LIFE:  
6,000 Cycles [cURus]

INGRESS PROTECTION:  
IP55

APPROVALS:  
 RoHS COMPLIANT

COLORS AND MARKINGS

BEZEL:  
Yellow

ACTUATOR:  
ON: Green  
OFF: Red

MARKING:  
I/O Horizontal (2)

MARKING COLOR:  
White

MATERIALS

UPPER BODY:  
Polyamide 6/6 (PA66)

LOWER BODY:  
Polyamide 6/6 (PA66+G10)

BEZEL:  
Polyamide 6/6 (PA66+G10)

ACTUATORS:  
Polyamide 6/6 (PA66)

MOUNTING EARS:  
Polyamide 6/6 (PA66)

CONTACTS:  
Silver Alloy Clad Copper (AgSnO/Cu)

TERMINALS:  
Brass

BODY	A	09/08/07	CAB
COLORS	A	09/08/07	CAB
MATERIALS	A	09/08/07	CAB
SPECIFICATIONS	A	09/08/07	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

REV.	A	INITIAL RELEASE DESCRIPTION	21997	6/30/2015	MW
			PCR	DATE	DRAWN BY

DIMENSIONS	INCHES [MILLIMETERS]
GENERAL TOLERANCES	±0.020 [±0.5] / ±1°
SCALE	DRAWING NOT TO SCALE

TITLE KJD17-21521-612	
ITEM NUMBER 34-KJD1721521612	DATE 6/30/2015
REVISION A	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[KJD17-21521-612](#)